

View Online at <https://aerobasegroup.com/nsn/5925-01-591-5078>

Body Style:

Multipole-multiple actuator type

Body Length:

80.0 millimeters

Body Width:

35.0 millimeters

Body Height:

61.5 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

17.5 millimeters

Boss Height:

17.5 millimeters

Pole Quantity:

2

Mounting Facility Type And Quantity:

Din rail

Maximum Continuous Load Current Rating Per Pole:

4.0 amperes ac all locations and 4.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

415.0 ac all locations and 125.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one and at pole two

Trip Delay Time In Seconds Per Rated Continuous Current:

30.000 at 800 pct pascal all locations and 120.000 18 stage pascal all locations

Trip Release Ambient Temperature Rating:

30.0 degrees celsius all locations

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0