

View Online at <https://aerobasegroup.com/nsn/5925-01-591-6139>

Body Style:

Multipole-multiple actuator type

Body Length:

105.0 millimeters

Body Width:

53.1 millimeters

Body Height:

44.0 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

17.7 millimeters

End Application:

Aircraft c295

Boss Height:

16.0 millimeters

Pole Quantity:

3

Mounting Facility Type And Quantity:

Din rail

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations and 10.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

277.0 ac all locations and 480.0 ac all locations and 96.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one and at pole two and at pole three

External Actuator Linkage Arrangement:

One, two, and three linked

Trip Delay Time In Seconds Per Rated Continuous Current:

20.000 at 800 pct pascal all locations and 90.000 18 stage pascal all locations

Product Name:

Faz na branch circuit breaker type d for highly inductive load

Special Features:

Suitable for applications where high levels of inrush current are expected; prevents nuisance tripping in high inductive apps

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0