NSN 5925-01-591-6702

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-591-6702 **Body Style:** Single pole type **Body Length:** 2.490 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.940 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.660 inches **Boss Height:** 0.314 inches **Mounting Surface To Terminal End Distance:** 2.325 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 65.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 7500.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 1000.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 flat rocker

Actuator Function:

Trip-reset

NSN 5925-01-591-6702

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 800 pct pascal single location and 150.000 18 stage pascal single location

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0