

View Online at <https://aerobasegroup.com/nsn/5925-01-592-0051>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.750 inches

Body Length:

2.000 inches

Body Width:

1.515 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

End Application:

Boat, barrier, 25ft, 25bb601 through 25bb606

Mounting Surface To Terminal End Distance:

2.200 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing

Maximum Continuous Load Current Rating Per Pole:

2.5 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations and 65.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.500 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.300 at 800 pct pascal all locations and 20.000 18 stage pascal all locations

Product Name:

Upg series magnetic circuit breaker, panel seal, one bat handle per unit, two pole, screw terminals, series, 2.5 amp, dc 50/60hz, long delay

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

Unf

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0