

View Online at <https://aerobasegroup.com/nsn/5925-01-592-2356>

Body Style:

Rectangular dimensional envelope

Overall Length:

2.250 inches

Overall Height:

4.260 inches

Overall Width:

1.256 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.172 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac single location and 7.5 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3600.0 ac single location and 3600.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

11.000 at 800 pct pascal single location and 40.000 18 stage pascal single location

Trip Release Ambient Temperature Rating:

-54.0 degrees celsius single location and 71.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0