## NSN 5925-01-592-2356

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-592-2356

**Body Style:** Rectangular dimensional envelope **Overall Length:** 2.250 inches **Overall Height:** 4.260 inches **Overall Width:** 1.256 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.172 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 7.5 amperes ac single location and 7.5 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3600.0 ac single location and 3600.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 1000.0 single location **Reset Method:** Automatic **Internal Trip Release Configuration:** Series trip single location **Trip Delay Time In Seconds Per Rated Continuous Current:** 11.000 at 800 pct pascal single location and 40.000 18 stage pascal single location **Trip Release Ambient Tempurature Rating:** -54.0 degrees celsius single location and 71.0 degrees celsius single location Frequency In Hertz: 400.0 single location **Terminal Type And Quantity:** 2 threaded stud

## NSN 5925-01-592-2356

Circuit Breaker - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0