

View Online at <https://aerobasegroup.com/nsn/5925-01-593-8344>

Body Style:

Single pole type

Bushing Length:

0.240 inches

Body Length:

2.000 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

End Application:

Boat, rigid, inflatable 5 meter, 5mrx0608; boat, rigid, inflatable 5 meter, 5mrx0801

Mounting Surface To Terminal End Distance:

1.697 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

80.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.100 at 200 pct single location and 1.200 at 200 pct single location

Product Name:

Cage: hydraulic magnetic circuit breaker, iug type, single toggle handle, sealed toggle with bushing mounting, single pole, series, dc short delay, screw terminals, trip-free

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0