NSN 5925-01-593-8499

Circuit Breaker - Page 1 of 1

Fiig: A030a0



View Online at https://aerobasegroup.com/nsn/5925-01-593-8499 **Body Style:** Multipole-single actuator type **Body Width:** 2.000 inches **Body Height:** 4.560 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 6.350 inches **End Application:** Panel, distribution; sentinel class fast response cutter b (frc-b) **Pole Quantity:** 2 **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 480.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 18000.0 ac all locations and 30000.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Trip Release Ambient Tempurature Rating:** 40.0 degrees celsius all locations **Product Name:** Circuit breaker **Special Features:** Wire size 12 to 10 awg (aluminum), 14 to 10 awg (copper); approval ul 489, csa 22.2; cms data id 1603, pccn se0372, plisn a004 Shelf Life: N/a **Unit Of Measure: Demilitarization:** No