# NSN 5925-01-595-6276



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-595-6276 **Body Style:** Multipole-multiple actuator type **Body Length:** 1.250 inches **Body Width:** 1.320 inches **Body Height:** 2.000 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 0.625 inches **End Application:** B-1 **Boss Height:** 0.125 inches **Pole Quantity:** 2 **Mounting Facility Type And Quantity:** Snap-in **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 800.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 

Rocker, 2

**Internal Trip Release Configuration:** 

Series trip all locations

# NSN 5925-01-595-6276

Circuit Breaker - Page 2 of 2



# **Trip Delay Time In Seconds Per Rated Continuous Current:**

3.000 at 200 pct all locations and 30.000 at 200 pct all locations

#### **Product Name:**

Cage: airpax type 203 magnetic supplementary protector with inverse delay, trip-free and illuminated handle features

## **Special Features:**

Rocker handles, ul/csa construction; black body; white translucent neon illuminated handles; 50/60 hz motor start dela with inertia delay added

# Frequency In Hertz:

50.0 all locations or 60.0 all locations

## **Terminal Type And Quantity:**

4 knife blade

Shelf Life:

N/a

Unit Of Measure:

**Demilitarization:** 

No

Fiig:

A030a0