

View Online at <https://aerobasegroup.com/nsn/5925-01-595-6276>

Body Style:

Multipole-multiple actuator type

Body Length:

1.250 inches

Body Width:

1.320 inches

Body Height:

2.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

End Application:

B-1

Boss Height:

0.125 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

Snap-in

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

800.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

Rocker, 2

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct all locations and 30.000 at 200 pct all locations

Product Name:

Cage: airpax type 203 magnetic supplementary protector with inverse delay, trip-free and illuminated handle features

Special Features:

Rocker handles, ul/csa construction; black body; white translucent neon illuminated handles; 50/60 hz motor start dela with inertia delay added

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

4 knife blade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0