

View Online at <https://aerobasegroup.com/nsn/5925-01-596-0169>

Body Style:

Multipole-single actuator type

Bushing Length:

0.240 inches

Body Length:

2.000 inches

Body Width:

2.265 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

End Application:

B-1

Mounting Surface To Terminal End Distance:

1.687 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22.5 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

12.000 at 200 pct all locations and 350.000 at 200 pct all locations

Special Features:

1 toggle handle per unit; sealed toggle w/bushing mounting; 3 pole; screw terminals w/barriers; series w/aux; 110 quick conn; 400 hz motor start delay; 150% trip; additional inertial delay

Frequency In Hertz:

400.000 all locations 60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0