

View Online at <https://aerobasegroup.com/nsn/5925-01-596-0169>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.240 inches

**Body Length:**

2.000 inches

**Body Width:**

2.265 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Unthreaded Mounting Hole Diameter:**

0.156 inches

**End Application:**

B-1

**Mounting Surface To Terminal End Distance:**

1.687 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

22.5 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

1000.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip w/auxiliary load terminal all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

12.000 at 200 pct all locations and 350.000 at 200 pct all locations

**Special Features:**

1 toggle handle per unit; sealed toggle w/bushing mounting; 3 pole; screw terminals w/barriers; series w/aux; 110 quick conn; 400 hz motor start delay; 150% trip; additional inertial delay

**Frequency In Hertz:**

400.000 all locations 60.0 all locations

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0