

View Online at <https://aerobasegroup.com/nsn/5925-01-596-0304>

Body Style:

Single pole type

Bushing Length:

0.240 inches

Body Length:

2.000 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.059 inches

End Application:

B-1

Mounting Surface To Terminal End Distance:

2.075 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

4.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

80.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

50.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal single location

Thread Size:

0.500 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 200 pct single location and 10.000 at 200 pct single location

Special Features:

1 toggle handle; sealed toggle w/bushing mounting; single pole; screw terminals; series w/aux switch 110 quick conn; dc short delay

Thread Series Designator:

Un

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0