

View Online at <https://aerobasegroup.com/nsn/5925-01-598-3939>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.0 inches

**Body Width:**

1.515 inches

**Center To Center Distance Between Terminals Parallel To Length:**

1.56 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.66 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.75 inches

**End Application:**

0000-1-Ig9-7307; mpd 85-015 (60955); p/n mpd 85-015

**Mounting Surface To Terminal End Distance:**

2.0 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

3000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic-hydraulic single location

**Trip Release Characteristic:**

Instantaneous single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**External Actuator Linkage Arrangement:**

One and two linked

**Internal Trip Release Configuration:**

Series trip single location

**Trip Release Duty Cycle:**

Continuous single location

**Product Name:**

Breaker, circuit

**Special Features:**

Cms data id 2958, pccn, plisn a003

**Terminal Type And Quantity:**

4 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0