

View Online at <https://aerobasegroup.com/nsn/5925-01-598-7114>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

Between 1.969 inches and 2.031 inches

**Body Width:**

1.515 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.499 inches and 1.561 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.735 inches and 0.765 inches

**Mounting Surface To Terminal End Distance:**

2.087 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

7.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Trip Release Method:**

Magnetic all locations

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Thread Size:**

0.500 inches

**Special Features:**

The "c" that replaced the slash in the milspec part number means that this is without either high-inrush feature or auxiliary contacts.

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0