

View Online at <https://aerobasegroup.com/nsn/5925-01-599-1920>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

3.75 inches

**Body Width:**

3.0 inches

**Body Height:**

2.375 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.0 inches

**End Application:**

Panel, emergency lighting distribution; sentinel class fast response cutter b (frc-b)

**Boss Height:**

0.625 inches

**Pole Quantity:**

3

**Maximum Continuous Load Current Rating Per Pole:**

80.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal-magnetic single location

**Trip Release Characteristic:**

Instantaneous single location

**Reset Method:**

Manual

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Product Name:**

Circuit breaker

**Special Features:**

Suffix m for marine 50 degrees c ambient calibration; cms data id 1660, pccn se0363, plisn a002

**Frequency In Hertz:**

60.0 single location

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0