

View Online at <https://aerobasegroup.com/nsn/5925-01-604-3995>

Body Style:

Single pole type

Body Length:

2.0 inches

Body Width:

0.75 inches

Center To Center Distance Between Terminals Parallel To Length:

1.53 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.66 inches

End Application:

Boat, rigid i

Mounting Surface To Terminal End Distance:

2.075 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 dc single location

Circuit Protection Type:

Reverse current single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Reset Method:

Manual

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.2 at 100 pct single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0