NSN 5925-01-604-4008

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-604-4008 **Body Style:** Single pole type **Body Length:** 2.0 inches **Body Width:** 0.75 inches Center To Center Distance Between Terminals Parallel To Length: 1.53 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.66 inches **End Application:** Boat, rigid i **Mounting Surface To Terminal End Distance:** 2.075 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 7500.0 dc single location **Circuit Protection Type:** Reverse current single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Reset Method:**

Manual **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Internal Trip Release Configuration:** Series trip single location **Thread Size:** 0.138 inches

NSN 5925-01-604-4008

Circuit Breaker - Page 2 of 2



Trin	Delay	Time	In	Seconds	Por	Rated	Continuous	Current.
ull	Delay	HIIIIE	111	Seconds	rei	Raieu	Continuous	Current.

1.2 at 100 pct single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A030a0