

View Online at <https://aerobasegroup.com/nsn/5925-01-608-5699>

Body Style:

Single pole type

Bushing Length:

Between 0.845 inches and 1.125 inches

Body Length:

0.781 inches

Body Width:

0.593 inches

Center To Center Distance Between Terminals Parallel To Length:

0.500 inches

Mounting Surface To Terminal End Distance:

1.343 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 terminal

Maximum Continuous Load Current Rating Per Pole:

2.5 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location

Trip Release Characteristic:

Time delay single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Trip Delay Time In Seconds Per Rated Continuous Current:

1.500 at 200 pct and 40.000 at 200 pct and 0.150 at 500 pct and 3.000 at 500 pct and 0.350 at 1000 pct and 0.800 at 1000 pct single location

Frequency In Hertz:

400.0 single location

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0