

View Online at <https://aerobasegroup.com/nsn/5925-01-608-8054>

Body Style:

Single pole type

Overall Length:

1.811 inches

Overall Height:

0.575 inches

Overall Width:

1.15 inches

Body Diameter:

0.433 inches

Bushing Length:

0.4961 inches

Body Length:

0.889 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.689 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.689 inches

End Application:

3895-01-577-2425, paving machine, bituminous material

Boss Height:

0.059 inches

Mounting Surface To Terminal End Distance:

0.378 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

Reset Method:

Manual

Thread Size:

12.0 millimeters

Thread Pitch In Millimeters:

1.0

Trip Delay Time In Seconds Per Rated Continuous Current:

5.0 at 200 pct and 40.0 at 200 pct all locations

Thread Tolerance Class:

-12x1 external

Product Name:

Thermal circuit breaker

Packaged Unit Weight:

0.5 ounces

Thread Series Designator:

M

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0