

View Online at <https://aerobasegroup.com/nsn/5925-01-613-0631>

Body Style:

Multipole-multiple actuator type

Body Length:

2.490 inches

Body Width:

2.265 inches

Center To Center Distance Between Terminals Parallel To Length:

1.94 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

End Application:

Nsn: 5895-01-572-8295, central communications; next assembly tac hub

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

2.404 inches

Pole Quantity:

3

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Position Designation:

At each pole

Trip Release Duty Cycle:

Continuous all locations

Switch Location And Position Designation:

External at each pole

Trip Release Ambient Temperature Rating:

70.0 degrees fahrenheit all locations

Special Features:

Operating temp range: -40 to +185 degrees f. Non-operating: -70 to +185 degrees f.; pole 2 is series trip w/auxiliary

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0