

View Online at <https://aerobasegroup.com/nsn/5925-01-613-0631>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.490 inches

**Body Width:**

2.265 inches

**Center To Center Distance Between Terminals Parallel To Length:**

1.94 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.060 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**End Application:**

Nsn: 5895-01-572-8295, central communications; next assembly tac hub

**Boss Height:**

0.140 inches

**Mounting Surface To Terminal End Distance:**

2.404 inches

**Pole Quantity:**

3

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Position Designation:**

At each pole

**Trip Release Duty Cycle:**

Continuous all locations

**Switch Location And Position Designation:**

External at each pole

**Trip Release Ambient Temperature Rating:**

70.0 degrees fahrenheit all locations

**Special Features:**

Operating temp range: -40 to +185 degrees f. Non-operating: -70 to +185 degrees f.; pole 2 is series trip w/auxiliary

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0