

View Online at <https://aerobasegroup.com/nsn/5925-01-613-5685>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.500 inches

**Body Width:**

1.515 inches

**Center To Center Distance Between Terminals Parallel To Length:**

1.940 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.062 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Boss Height:**

0.150 inches

**Mounting Surface To Terminal End Distance:**

2.723 inches

**Pole Quantity:**

2

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

80.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

62.5 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Nontrip free

**Trip Delay Time In Seconds Per Rated Continuous Current:**

45.0 at 125 pct and 345.0 at 125 pct all locations

**Product Name:**

C series, circuit breaker

**Special Features:**

Used on boatalt 38rp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0