

View Online at <https://aerobasegroup.com/nsn/5925-01-617-4491>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.370 inches

**Body Length:**

1.562 inches

**Body Width:**

1.281 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.875 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.625 inches

**Unthreaded Mounting Hole Diameter:**

0.147 inches

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Length:**

0.075 inches

**Nonturn Device Width:**

0.125 inches

**End Application:**

Ssds mk2, mod

**Mounting Surface To Terminal End Distance:**

0.380 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

2 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

4.0 amperes ac and 4.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc and 240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

4.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

400.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

0.015 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

Between pole one and two

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Release Duty Cycle:**

Continuous all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

3.0 at 150 pct and 70.0 at 150 pct and 0.05 at 200 pct and 20.0 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Shock resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Product Name:**

Circuit breaker

**Frequency In Hertz:**

400.0 all locations

**Test Data Document:**

Mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 wire hook

**Specification Data:**

-mil-prf-39019 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

1-000-0

**Mil-std (military Standard):**

Mil-prf-39019 spec.