

View Online at <https://aerobasegroup.com/nsn/5925-01-619-2942>

**Body Style:**

Multipole-single actuator type

**Body Length:**

6.40 inches

**Body Width:**

2.74 inches

**Body Height:**

3.44 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

5.52 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.38 inches

**Unthreaded Mounting Hole Diameter:**

0.20 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

5.66 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.37 inches

**Boss Height:**

0.30 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

100.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac and 250.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

80.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Nontrip free

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Product Name:**

H frame circuit breaker

**Frequency In Hertz:**

50.0 all locations

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0