

View Online at <https://aerobasegroup.com/nsn/5925-01-619-2942>

Body Style:

Multipole-single actuator type

Body Length:

6.40 inches

Body Width:

2.74 inches

Body Height:

3.44 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.52 inches

Center To Center Distance Between Terminals Parallel To Width:

1.38 inches

Unthreaded Mounting Hole Diameter:

0.20 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.66 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.37 inches

Boss Height:

0.30 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac and 250.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

80.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Product Name:

H frame circuit breaker

Frequency In Hertz:

50.0 all locations

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0