

View Online at <https://aerobasegroup.com/nsn/5925-01-620-5007>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.500 inches

**Body Width:**

3.00 inches

**Body Height:**

3.00 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Pole Quantity:**

4

**Mounting Facility Type And Quantity:**

8 threaded stud

**Thready Qty Per Inch (tpi):**

20

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations

**Circuit Protection Type:**

Error current all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

120.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Nontrip free

**Manual Actuator Type And Quantity:**

4 toggle

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.25 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

18.0 at 100 pct all locations

**Product Name:**

Hydraulic magnetic circuit breaker

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

8 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0