

View Online at <https://aerobasegroup.com/nsn/5925-01-620-5008>

Body Style:

Single pole type

Body Length:

2.50 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

2.00 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded stud

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

65.0 dc all locations

Circuit Protection Type:

Error current all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

120.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

10.0 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

18.0 at 100 pct all locations

Product Name:

Hydraulic magnetic circuit breaker

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unf

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0