## NSN 5925-01-626-3349

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-626-3349

| Body Style:   |
|---|
| Single pole type  |
| Bushing Length:   |
| Between 0.332 inches and 0.380 inches                           |
| Body Length:  |
| 1.562 inches  |
| Body Width:   |
| 0.625 inches  |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.906 inches  |
| End Application:  |
| 5840-01-412-9653  |
| Mounting Surface To Terminal End Distance:                      |
| 1.810 inches  |
| Pole Quantity:  |
| 1   |
| Mounting Facility Type And Quantity:                            |
| 1 threaded bushing  |
| Maximum Continuous Load Current Rating Per Pole:                |
| 3.0 amperes ac and 3.0 amperes dc single location               |
| Operating Voltage Type And Rating Per Pole In Volts:            |
| 240.0 ac and 50.0 dc single location                            |
| Circuit Protection Type:  |
| Overcurrent single location                                     |
| Trip Release Method:  |
| Magnetic single location  |
| Trip Release Characteristic:                                    |
| Time delay single location                                      |
| Reset Method:   |
| Manual  |
| Main Contact Tripping Mechanism Type:                           |
| Trip free   |
| Manual Actuator Type And Quantity:                              |
| 1 toggle  |
| Actuator Function:  |
| Trip-reset  |
| Thread Size:  |
| 0.375 inches  |
| Trip Delay Time In Seconds Per Rated Continuous Current:        |
| 3.0 at 135 pct and 60.0 at 135 pct single location              |
| Frequency In Hertz:   |
| 400.0 single location   |
|   |

## NSN 5925-01-626-3349

Circuit Breaker - Page 2 of 2

**Thread Series Designator:** 

Unef

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0

