

View Online at <https://aerobasegroup.com/nsn/5925-01-626-3349>

Body Style:

Single pole type

Bushing Length:

Between 0.332 inches and 0.380 inches

Body Length:

1.562 inches

Body Width:

0.625 inches

Center To Center Distance Between Terminals Parallel To Length:

0.906 inches

End Application:

5840-01-412-9653

Mounting Surface To Terminal End Distance:

1.810 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac and 3.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac and 50.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

3.0 at 135 pct and 60.0 at 135 pct single location

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0