## NSN 5925-01-626-7676



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-626-7676 **Body Style:** Multipole-single actuator type **Body Length:** 5.125 inches **Body Width:** 3.485 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 2.286 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.026 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.026 inches **Boss Height:** 0.219 inches **Mounting Surface To Terminal End Distance:** 3.485 inches **Pole Quantity:** 2 **Mounting Facility Type And Quantity:** 4 threaded hole **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 125.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic-hydraulic all locations **Trip Release Characteristic:** Time delay all locations **Reset Method:** Manual

**Main Contact Tripping Mechanism Type:** 

Nontrip free

**Internal Trip Release Configuration:** 

Series trip all locations

**Thread Size:** 

0.1302 inches

## NSN 5925-01-626-7676

Circuit Breaker - Page 2 of 2

**Fiig:** A030a0



Trip Delay Time In Seconds Per Rated Continuous Current:
2.0 at 100 pct all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No