

View Online at <https://aerobasegroup.com/nsn/5925-01-627-1697>

Body Style:

Multipole-single actuator type

Body Length:

6.500 inches

Body Width:

4.125 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

3.3125 inches

Center To Center Distance Between Terminals Parallel To Width:

3.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.3125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Boss Height:

0.187 inches

Mounting Surface To Terminal End Distance:

4.125 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Features Provided:

Interchangeable trip release

Maximum Continuous Load Current Rating Per Pole:

100.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

25.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 dc all locations

Circuit Protection Type:

Undervoltage all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

2 alarm

Adjustable Trip Setting Current Range Per Pole In Amps:

+600.0 to 700.0 dc all locations

Internal Trip Release Configuration:

Shunt trip all locations

Inclosure Protection Type For Which Designed:

Shock resistant and fungus resistant

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Switch Terminal Type:

Wire lead

Product Name:

Nqb-a101 120 vdc shunt trip a/b auxillary

Special Features:

Works as a disconnect - does not include an automatic opening device

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Terminal Type And Quantity:

6 threaded stud

Specification Data:

81349-mil-dtl-17361/4b government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0