

View Online at <https://aerobasegroup.com/nsn/5925-01-629-6711>

Body Style:

Multipole-single actuator type

Overall Length:

2.06 inches

Overall Height:

3.22 inches

Overall Width:

1.53 inches

Body Length:

3.04 inches

Body Width:

2.01 inches

Body Height:

1.45 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.94 inches

Center To Center Distance Between Terminals Parallel To Width:

0.74 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.94 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.94 inches

End Application:

Control cabinet

Boss Height:

0.14 inches

Mounting Surface To Terminal End Distance:

2.6 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

1

Maximum Continuous Load Current Rating Per Pole:

40.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Circuit Protection Type:

Overvoltage all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Electric

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Relay trip all locations

Thread Size:

0.25 inches

Reset Actuator Voltage Rating And Type In Volts:

120.0 ac

Trip Delay Time In Seconds Per Rated Continuous Current:

0.12 at 125 pct all locations

Product Name:

Circuit breaker

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Un

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0