

View Online at <https://aerobasegroup.com/nsn/5925-01-641-9448>

Body Style:

Multipole-multiple actuator type

Bushing Length:

16.66 millimeters

Body Length:

51.59 millimeters

Body Width:

38.48 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

39.65 millimeters

Center To Center Distance Between Terminals Parallel To Width:

19.43 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

39.65 millimeters

Mounting Surface To Terminal End Distance:

56.69 millimeters

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Thread Size:

4.0 inches

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unf

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0