

View Online at <https://aerobasegroup.com/nsn/5925-01-642-5196>

Body Style:

Multipole-multiple actuator type

Body Length:

63.25 millimeters

Body Width:

57.53 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

33.32 millimeters

Center To Center Distance Between Terminals Parallel To Width:

19.05 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

33.32 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

19.05 millimeters

Boss Height:

3.30 millimeters

Mounting Surface To Terminal End Distance:

51.82 millimeters

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded stud

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

277.0 ac and 480.0 ac all locations

Circuit Protection Type:

Undercurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Internal Trip Release Configuration:

Series trip all locations

Switch Current Rating And Type In Amps:

20.0 ac

Product Name:

Magnetic circuit protector

Special Features:

3 poles, 5 amp rated current

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0