

View Online at <https://aerobasegroup.com/nsn/5925-01-642-5204>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

63.25 millimeters

**Body Width:**

57.53 millimeters

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

33.32 millimeters

**Center To Center Distance Between Terminals Parallel To Width:**

19.05 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

33.32 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

19.05 millimeters

**Boss Height:**

3.30 millimeters

**Mounting Surface To Terminal End Distance:**

51.82 millimeters

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 threaded stud

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

277.0 ac and 480.0 ac all locations

**Circuit Protection Type:**

Undercurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Internal Trip Release Configuration:**

Series trip all locations

**Product Name:**

Magnetic circuit protector

**Special Features:**

3 poles, 3 amp rated current

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0