

View Online at <https://aerobasegroup.com/nsn/5925-01-644-8441>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.625 inches

**Body Length:**

2.490 inches

**Body Width:**

1.515 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.312 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Unthreaded Mounting Hole Diameter:**

0.515 inches

**End Application:**

Battery charger

**Mounting Surface To Terminal End Distance:**

2.040 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

1 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

7.50 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

1.0 at 125 pct all locations

**Product Name:**

Circuit breaker

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0