

View Online at <https://aerobasegroup.com/nsn/5925-01-644-8441>

Body Style:

Multipole-single actuator type

Bushing Length:

0.625 inches

Body Length:

2.490 inches

Body Width:

1.515 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.312 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.515 inches

End Application:

Battery charger

Mounting Surface To Terminal End Distance:

2.040 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

7.50 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

1.0 at 125 pct all locations

Product Name:

Circuit breaker

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0