

View Online at <https://aerobasegroup.com/nsn/5925-01-645-0713>

**Body Style:**

Multipole-single actuator type

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac and 250.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac single location

**Circuit Protection Type:**

Overvoltage single location

**Trip Release Method:**

Magnetic-hydraulic single location

**Trip Release Characteristic:**

Time delay single location

**Reset Method:**

Automatic

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Position Designation:**

Between pole one and two

**Product Name:**

Hydraulic-magnetic circuit breaker

**Special Features:**

8mm spacing between operator and any other conductive surface; dielectric withstand-3750v ac; higher dc voltage rating for telecom applications; tamper-proof terminals. Trip free feature helps prevent the circuit breaker from being held in the on position during an overload.

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0