

View Online at <https://aerobasegroup.com/nsn/5925-01-645-0713>

Body Style:

Multipole-single actuator type

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 threaded hole

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac and 250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

Circuit Protection Type:

Overvoltage single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Reset Method:

Automatic

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Position Designation:

Between pole one and two

Product Name:

Hydraulic-magnetic circuit breaker

Special Features:

8mm spacing between operator and any other conductive surface; dielectric withstand-3750v ac; higher dc voltage rating for telecom applications; tamper-proof terminals. Trip free feature helps prevent the circuit breaker from being held in the on position during an overload.

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0