

View Online at <https://aerobasegroup.com/nsn/5925-01-649-3262>

Body Style:

Multipole-single actuator type

Body Length:

2.00 inches

Body Width:

1.515 inches

Body Height:

2.256 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

2.00 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.00 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

End Application:

Boat patrol

Boss Height:

0.625 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 terminal

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

60.0 at 150 pct all locations

Inclosure Protection Type For Which Designed:

Salt spray proof and moisture resistant

Product Name:

Circuit breaker

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0