

View Online at <https://aerobasegroup.com/nsn/5925-01-649-3384>

**Body Style:**

Multipole-single actuator type

**Body Length:**

2.490 inches

**Body Width:**

1.515 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.940 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.44 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**End Application:**

65034-800 12c

**Boss Height:**

0.140 inches

**Mounting Surface To Terminal End Distance:**

1.859 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

2 threaded stud

**Thready Qty Per Inch (tpi):**

20

**Maximum Continuous Load Current Rating Per Pole:**

2.50 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Auxiliary Switch Function And Quantity:**

1 control

**Thread Size:**

0.25 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

7.0 at 150 pct all locations

**Inclosure Protection Type For Which Designed:**

Salt spray proof and moisture resistant

**Product Name:**

Ckt, brkd 2.5amp

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0