

View Online at <https://aerobasegroup.com/nsn/5925-01-649-3392>

Body Style:

Multipole-single actuator type

Body Length:

2.490 inches

Body Width:

1.515 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.44 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

End Application:

65034-800 12c

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

1.859 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 threaded stud

Thready Qty Per Inch (tpi):

20

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Auxiliary Switch Function And Quantity:

1 control

Thread Size:

0.25 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

60.0 at 150 pct all locations

Inclosure Protection Type For Which Designed:

Salt spray proof and moisture resistant

Product Name:

Ckt, brkr 2p, 20a

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0