

View Online at <https://aerobasegroup.com/nsn/5925-01-652-3550>

Body Style:

Multipole-multiple actuator type

Body Length:

69.60 millimeters

Body Width:

57.90 millimeters

Body Height:

50.80 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

49.28 millimeters

Center To Center Distance Between Terminals Parallel To Width:

19.05 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

52.37 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

19.05 millimeters

End Application:

Analyzer

Boss Height:

3.56 millimeters

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 threaded stud

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

32.0 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.9 at 200 pct all locations

Product Name:

Circuit breaker

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unf

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0