

View Online at <https://aerobasegroup.com/nsn/5925-01-654-8134>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.625 inches

**Body Length:**

2.00 inches

**Body Width:**

1.515 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**End Application:**

Boat, harbor

**Mounting Surface To Terminal End Distance:**

2.256 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

32.0 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.15 at 200 pct all locations

**Product Name:**

Circuit breaker

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0