

View Online at <https://aerobasegroup.com/nsn/5925-01-657-4797>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.150 inches

Body Length:

2.530 inches

Body Width:

1.515 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

End Application:

An/sqq-89 (v) 15j un 818 scp

Mounting Surface To Terminal End Distance:

2.645 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

2.0 at 200 pct and 20.0 at 200 pct all locations

Inclsure Protection Type For Which Designed:

Fungus proof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Product Name:

Circuit breaker 20a; hydraulic magnetic circuit protector

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0