

View Online at <https://aerobasegroup.com/nsn/5925-01-657-4849>

**Body Style:**

Multipole-multiple actuator type

**Bushing Length:**

0.150 inches

**Body Length:**

2.530 inches

**Body Width:**

1.515 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.940 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Unthreaded Mounting Hole Diameter:**

0.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.060 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**End Application:**

An/sqq-89 (v) 15j un 818 scp

**Mounting Surface To Terminal End Distance:**

2.645 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

35.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip w/auxiliary load terminal all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.0 at 200 pct and 20.0 at 200 pct all locations

**Inclsure Protection Type For Which Designed:**

Fungus proof

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Product Name:**

Circuit breaker 35a; hydraulic magnetic circuit protector

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

4 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0