## NSN 5930-00-001-3091

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-001-3091 **Thread Class:** 2b single mounting facility **Overall Length:** 11.000 inches **Overall Height:** 2.375 inches **Overall Width:** 2.375 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 2.000 inches single actuator **Individual Section Quantity:** 8 **Longest Horizontal Distance Between Mounting Centers:** 1.250 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 6th section front **Throw Quantity:** 10 4th section front **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 120.0 ac at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 10 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug and turret **Contact Switching Action:** Breaks before makes 8th section front **Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## **NSN 5930-00-001-3091**Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
15.0 amperes resistive load ac at sea level
Precious Material And Location:
Contact surfaces gold and contacts and wipers silver
Precious Material:
Gold and silver
Style Designator:
Tap, square frame
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0