

View Online at <https://aerobasegroup.com/nsn/5930-00-001-3172>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof

Body Diameter:

0.720 inches

Bushing Length:

Between 0.745 inches and 0.805 inches

Body Length:

1.200 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.245 inches and 0.255 inches

Actuator Height:

0.250 inches

Actuator Free Position Height:

0.242 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

24.0 ounces

Switch Actuating Force:

96.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0