

View Online at <https://aerobasegroup.com/nsn/5930-00-001-5885>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof

Bushing Length:

Between 1.197 inches and 1.259 inches

Body Length:

Between 0.869 inches and 0.937 inches

Body Width:

Between 0.875 inches and 0.937 inches

Body Height:

Between 0.469 inches and 0.531 inches

Case Material:

Plastic

Actuator Style:

Roller plunger

Actuator Free Position Height:

0.147 inches

Actuator Roller Diameter:

0.312 inches

Actuator Roller Width:

0.120 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.438 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

96.0 ounces

Actuator Movement:

0.100 pretravel inches and 0.125 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Terminals on base end of switch

Thread Series Designator:

Un

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0